

WHAT IS CLAIMED IS:

1. A fiber-semiconductor laser source  
comprising an optically pumped VCSEL and a fiber  
5 amplifier for the laser output of said VCSEL which are  
optically pumped by a common optical pump source.

2. A laser source according to claim 1 wherein  
said optical pump source produces a pump laser output  
10 with a wavelength  $\lambda_1$  and said VCSEL produces a VCSEL  
laser output with a wavelength  $\lambda_2$ .

3. A laser source according to claim 2 wherein  
said optical pump source is a diode laser.

4. A laser source according to claim 3 further  
including means for deriving first and second pump  
laser beams from the laser output of said diode laser,  
first means for injecting said first laser beam into  
20 said VCSEL and second means for injecting said second  
laser beam into said fiber amplifier.

5. A laser source according to claim 4 wherein said fiber amplifier comprises a doped optical fiber, and further including means for injecting said VCSEL laser output into said fiber and means for extracting the amplified VCSEL laser output from said fiber.

6. A laser source according to claim 1 wherein said fiber amplifier comprises a doped optical fiber having one end disposed to inject said pump laser output into said VCSEL whereby to cause said VCSEL to produce said VCSEL laser output, and further including a multiplexer connected to the opposite end of said doped optical fiber and coupled to said optical pump source for (a) injecting said pump laser output into said fiber and (b) coupling said VCSEL laser output to an optical device.

7. An efficient laser source comprising a pump laser for emitting a pump laser beam at a wavelength  $\lambda_1$ , a vertical cavity surface emitting laser (VCSEL),

means for directing said pump laser beam into said VCSEL so as to cause said VCSEL to emit a VCSEL laser beam at a wavelength  $\lambda_2$ , an optical gain fiber, and light coupling means for (a) directing said VCSEL laser beam into said optical gain fiber and (b) injecting said pump laser beam into said optical gain fiber so as to provide amplification for said VCSEL laser beam.

8. A laser source according to claim 7 wherein said pump laser beam is collimated, and further wherein said light coupling means comprises:

a first diachronic beam splitter which is adapted to reflect and transmit light of wavelength  $\lambda_1$  and to transmit light of wavelength  $\lambda_2$ , said beam splitter being disposed so as to reflect a portion of said pump laser beam into said VCSEL and also to receive and transmit the VCSEL laser beam emitted by said VCSEL;

a second polarization dependent beam splitter disposed to receive the VCSEL laser beam output from first beam splitter, said second beam splitter being

adapted to reflect said VCSEL laser beam according to a first VCSEL beam polarization and to transmit said same laser beam according to a second polarization rotated 90 degrees from said first beam polarization;

5 means for receiving said VCSEL laser beam reflected by said second beam splitter and injecting same into one end of said optical gain fiber;

reflector means for injecting said pump laser beam into said optical gain fiber;

10 a Faraday rotator mirror coupled to the opposite end of said optical gain fiber for receiving the VCSEL laser beam reflected from said second beam splitter, rotate the beam polarization by 90 degrees, and reflect the VCSEL beam with rotated polarization back  
15 along optical gain fiber for transmittal through said second beam splitter; and

optical output means for receiving the reflected VCSEL laser beam with rotated polarization that is transmitted through said second beam splitter.

20

9. An improved laser source comprising:

a vertical cavity surface emitting laser (VCSEL);  
a pump laser for generating a single mode output  
beam at a wavelength  $\lambda_1$ ;

diachronic beam splitter means for receiving said  
5 pump laser output beam and dividing the power of that  
beam so as to form a first and second beams of like  
wavelength  $\lambda_1$ , said beam splitter being positioned so  
that one of said beams is injected into said VCSEL so  
as to cause said VCSEL to emit a VCSEL laser beam at a  
10 wavelength  $\lambda_2$ ;

an optical gain fiber; and

15 light coupling means for directing said VCSEL  
laser beam into said optical gain fiber and for  
injecting the other of said first and second beams  
from said pump laser into said optical gain fiber so  
as to provide amplification for said VCSEL laser beam.

10. An improved laser source according to claim  
9 wherein the other of said first and second beams of  
20 wavelength  $\lambda_1$  is coupled to said gain fiber by  
reflection from a plurality of mirrors.

11. An improved laser source according to claim  
9 wherein said VCSEL has a movable mirror and a fixed  
internal mirror aligned with its vertical cavity, and  
5 further wherein said pump laser and said beam splitter  
are arranged so as to couple said one beam of  
wavelength  $\lambda_1$  to said VCSEL via transmittal through  
said fixed mirror.

12. An improved laser source according to claim  
9 wherein said VCSEL has a movable mirror and a fixed  
internal mirror aligned with its vertical cavity, and  
further wherein said pump laser and said beam splitter  
are arranged so as to couple said one beam of  
15 wavelength  $\lambda_1$  to said VCSEL via said transmittal  
through said movable mirror.

13. An improved laser source according to claim  
9 wherein said light coupling means comprises a  
20 diachronic mirror disposed so as to receive said VCSEL  
laser beam and the other of said first and second

beams from said pump laser and to direct them into  
said optical gain fiber.

14. An improved laser source according to claim  
5 9 further including an optical lens for directing said  
VSCEL laser beam and the other of said first and  
second beams from said pump laser into one end of said  
optical gain fiber.

15. An improved laser source comprising:  
a vertical cavity surface emitting laser (VCSEL);  
an optical gain fiber having one end optically  
coupled to the output side of said VCSEL;  
a pump laser for generating a single mode pump  
15 laser beam at a wavelength  $\lambda_1$ ; and

a wavelength division multiplexer having first  
and second input ports and an output port, with said  
first input port coupled to said gain fiber and said  
second input port coupled to said pump laser, said  
20 multiplexer being adapted to (a) inject said pump  
laser beam into said gain fiber to optically pump said

VCSEL and thereby cause it to emit a VCSEL laser beam that is injected into said one end of said gain fiber, and (b) pass said VCSEL from said gain fiber to said output port for extraction from said source, VCSEL laser beam being amplified by said gain fiber during its transit to said output port.

16. An improved laser source according to claim 15 wherein said pump laser is a pulse laser, and said multiplexer is adapted to alternately inject pump laser pulses into said VCSEL and to pass said amplified VCSEL laser beam to said output port.